## WEST BOND, INC.



## **7200CR SERIES**MANUAL EPOXY DIE BONDERS

Continuing a Tradition of Quality



The fully programmable Microprocessor Controlled dispensing of epoxy ensures precise dot size. Each **EPOXY DISPENSE HEAD** contains 2 <sup>5</sup>/<sub>8</sub>cc reservoirs for Epoxy. A variety of dispense needles are available to suit most applications. Dispense elevation is programmable. Following the dispense sequence; the machine automatically calls for the **VACUUM PICKUP TOOL** when the tool head assembly is lifted to a programmed elevation from the work. The Machine can be programmed for operator input to toggle between the **EPOXY DISPENSE TOOL** and the **VACUUM PICKUP TOOL** for pick and place operation.


The **VACUUM PICKUP TOOL** has a flat-faced Delrin tip with a vacuum through hole. A broad range of die sizes can be handled with a single tool. Die selected from practically any carrier media can be manipulated and rotated (360°) into position. Vacuum can be turned On or Off either by contact with the die surface or by control of the operator at any elevation.













## STANDARD SPECIFICATIONS:

CONTROL LOGIC: Motorola 68000 Microprocessor

MEMORY: 256KB RAM

DEVICE STORAGE: Single Device DISPLAY: 40 Character, 4 Line LCD Z-ENCODER RESOLUTION: 0.001"

TOOL Z RANGE: 0.6875" THROAT DEPTH: 5.25"

BOND FORCE RANGE: Adjustable, 5 – 75 grams

ESD PROTECTION: Protection against Electrostatic Discharge

PICK-UP TOOL LENGTH: 0.625"

EPOXY DISPENSE NEEDLE LENGTH: 0.400"

EPOXY DISPENSE NEEDLE BORE: 0.006" - 0.073"

MICROMANIPULATOR: Counterbalanced, single lever X-Y-Z/8:1 ratio WORK PLATFORM: Fixed height. Adjustable height priced & planarity

control sold separately

MICROSCOPE: Selection available, (ESD types available) ILLUMINATOR: Selection available, (ESD types available) WORK HOLDERS: Selection available, priced separately

## www.westbond.com

WEST-BOND INC.
WEST-BOND INTERNATIONAL INC.

1551 S. Harris Court, Anaheim, California 92806, U.S.A.

Phone: (714) 978-1551 Fax: (714) 978-0431

E-mail: sales@westbond.com